



EN ISO 20344:2011



HORIZON  
**ILLINOIS**  
52023-15L

**S3 SRC**

**Size:** 36-48  
**Weight:** 700 gr.

**Fit:** 10,5

**Working Environment:**  
Multipurpose, Building, Logistics and Light Industry, Farming and Gardening



**FEATURES**

**UPPER**  
Grain leather Hydro Fabric of High Tenacity

**LINING**  
3D Air circulation 320 gr.

**INSOLE**  
Climaction-Fit 337

**TOE CAP**  
Steel Toe Cap

**RESISTANCE TO PERFORATION**  
Steel Plate

**TYPE**  
Ankle boot

**SOLE**  
**PU DUAL-DENSITY SRC**  
Two-component PU sole with self-cleaning pattern, extremely flexible for various places of use, both indoor and outdoor, with SRC Antislip Standard.

**TECHNOLOGIES**

**Removable Insole** **337**  
**climaction fit**

Removable anatomic and ergonomic insole. Absorbent and transpiring open-cell foam support. Keeps feet fresh. Specifically-designed thermoforming for exceptional comfort.



**Protection elements**  
**STEEL PROTECTION**

Steel toecap, with anti-corrosion paint. Protection of over 200J. Comfortable fit. Stainless steel Plate resistant puncture with acid-resistant paint.



**SRC (SRA+SRB)**

SOLE 52 - 53 <b>PU - PU</b>		
<b>SRA</b> CERAMIC + DETERGENT SOLUTION	FLAT ≥0.32 HEEL (CONTACT ANGLE °) ≥0.28	<b>0.36</b> <b>0.42</b>
<b>SRB</b> STEEL + GLYCEROL	FLAT ≥0.18 HEEL (CONTACT ANGLE °) ≥0.13	<b>0.19</b> <b>0.14</b>

EN ISO 20344:2011


**Lateral stability**  
**dynamic HC control**  
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



**Torsional stability**  
**STABIL•ACTIVE**

It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



**Electrical features**  
**WED**

Wire Electricity Discharge  
Strip with 4 filaments of carbon fiber, ensuring proven anti-static properties of the footwear over time.



**Other**  
**DUAL MICRO DWT WICBO**

Double non-slip layer of microfibre, resistant up to 200,000 cycles. Makes the footwear more comfortable, blocking the foot during use.